



**Underwriters  
Laboratories Inc.®**

333 Pfingsten Road  
Northbrook, IL 60062-2096 USA  
www.ul.com  
tel: 1 847 272 8800  
fax: 1 847 272 8129  
Customer service: 1 877 854 3577

File E306665

Vol 1

Issued: 2006-10-30

Revised:

FOLLOW-UP SERVICE PROCEDURE  
(TYPE R)

OUTLET BUSHINGS AND FITTINGS  
(QCRV, QCRV7)

Manufacturer: SIB-ADR  
(192791-001) 50 RUE DU CAPITAINE MAILLARD  
57220 BOULAY FRANCE

Applicant: SAME AS MANUFACTURER  
(192791-001)

Listee: SAME AS MANUFACTURER  
(192791-001)

This Procedure authorizes the above manufacturer to use the marking specified by Underwriters Laboratories Inc. only on products covered by this Procedure, in accordance with the applicable Follow-Up Service Agreement.

The prescribed Mark or Marking shall be used only at the above manufacturing location on such products which comply with this Procedure and any other applicable requirements.

The Procedure contains information for the use of the above named Manufacturer and representatives of Underwriters Laboratories Inc. and is not to be used for any other purpose. It is lent to the Manufacturer with the understanding that it is not to be copied, either wholly or in part, and that it will be returned to Underwriters Laboratories Inc. upon request.

This PROCEDURE, and any subsequent revisions, is the property of UNDERWRITERS LABORATORIES INC. and is not transferable.

UNDERWRITERS LABORATORIES INC.

Sajeev Jesudas  
Chief Operating Officer



## DESCRIPTION

## PRODUCT COVERED:

USL, CNL Cord Connectors, Cat. Nos.

Metric hub long threads, F 7031 609, F 7032 009, F 7032 509, F 7032 559, F 7033 209, F 7034 009, F 7035 009, F 7036 309, F 8031 600, F 8032 000, F 8032 500, F 8032 550, F 8033 200, F 8034 000, F 8035 000, F 8036 300, F 7031 600, F 7032 000, F 7032 500, F 7032 550, F 7033 200, F 7034 000, F 7035 000, F 7036 300.

Metric hub long threads, F 7031 649, F 7032 049, F 7032 549, F 7033 249, F 7034 049, F 7035 049, F 7036 349, F 8031 640, F 8032 040, F 8032 540, F 8033 240, F 8034 040, F 8035 040, F 8036 340, F 7031 640, F 7032 040, F 7032 540, F 7033 240, F 7034 040, F 7035 040, F 7036 340.

PG hub standard threads, F 7000 909, F 7001 109, F 7001 309, F 7001 609, F 7002 109, F 7002 909, F 7003 609, F 7004 209, F 8000 900, F 8001 100, F 8001 300, F 8001 600, F 8002 100, F 8002 900, F 8003 600, F 8004 200, F 7000 900, F 7001 100, F 7001 300, F 7001 600, F 7002 100, F 7002 900, F 7003 600, F 7004 200, F 7004 900.

PG hub standard threads, F 7000 949, F 7001 149, F 7001 349, F 7001 649, F 7002 149, F 7002 949, F 7003 649, F 7004 249, F 7004 949, F 8000 940, F 8001 140, F 8001 340, F 8001 640, F 8002 140, F 8002 940, F 8003 640, F 8004 240, F 8004 940, F 7000 940, F 7001 140, F 7001 340, F 7001 640, F 7002 140, F 7002 940, F 7003 640, F 7004 240, F 7004 940.

Metric hub standard threads, F 7021 659, F 7021 609, F 7022 059, F 7022 009, F 7022 559, F 7022 509, F 7023 209, F 7024 009, F 7025 009, F 7026 309, F 8021 650, F 8021 600, F 8022 050, F 8022 000, F 8022 550, F 8022 500, F 8023 200, F 8024 000, F 8025 000, F 8026 300, F 7021 650, F 7021 600, F 7022 050, F 7022 000, F 7022 550, F 7022 500, F 7023 200, F 7024 000, F 7025 000, F 7026 300.

Metric hub standard threads, F 7021 669, F 7021 649, F 7022 069, F 7022 049, F 7022 569, F 7022 549, F 7023 249, F 7024 049, F 7025 049, F 7026 349, F 8021 660, F 8021 640, F 8022 060, F 8022 040, F 8022 560, F 8022 540, F 8023 240, F 8024 040, F 8025 040, F 8026 340, F 7021 660, F 7021 640, F 7022 060, F 7022 040, F 7022 560, F 7022 540, F 7023 240, F 7024 040, F 7025 040, F 7026 340.

NPT hub threads, F 7040 809, F 7041 209, F 7042 009, F 7042 809, F 8040 800, F 8041 200, F 8042 000, F 8042 800, F 7040 800, F 7041 200, F 7042 000, F 7042 800.

NPT hub threads, F 7040 849, F 7041 249, F 7042 049, F 7042 849, F 8040 840, F 8041 240, F 8042 040, F 8042 840, F 7040 840, F 7041 240, F 7042 040, F 7042 840.

## GENERAL:

The cord connectors covered by this Report are intended for use with specific sizes of cord to provide a smooth surface for the cord entering a box, and strain relief up to 35 lb for internal electrical connections. They are intended for indoor use in dry locations only. The PG and metric Series fittings are provided with PG or metric threads and intended for use in the European market. If PG or metric Series fittings are intended for domestic use, they must be provided with locknuts. See Ills. 1 - 3 for sizes and colors of each catalog number.